

Air or Nitrogen Hurricane Product Range



Booster Model	Engine	Suction P (psi / bar)	Discharge P (psi / bar)	Capacity @ Suction P (cfm / m3/min)
B4 - 41 / 750**	JD 4045	350 / 24	750 / 52	1800 / 51
B4 - 41 / 900*	CUM QSB 4.5L	350 / 24	900 / 62	1400 / 40
B4 - 41 / 1000**	JD 4045	350 / 24	1000 / 69	1400 / 40
B7 - 41 / 1000	CAT C7	350 / 24	1000 / 69	2440 / 69
B7 - 42 / 2175	CAT C7	350 / 24	2175 / 150	1288 / 37
B7 - 43 / 3000	CAT C7	150 / 10.3	3000 / 207	500 / 14
B7 - 43 / 4000	CAT C7	320 / 22	4000 / 276	750 / 21
B7 - 44 / 5000	CAT C7	261 / 18	5000 / 345	530 / 15
B9 - 64 / 5000	CAT C9	174 / 12	5000 / 345	550 / 16
B13 - 62 / 2175	CAT C13	350 / 24	2175 / 150	1800 / 51
B15 - 62 / 2175	CAT C15	350 / 24	2175 / 150	2250 / 64
B15 - 63 / 3000	CAT C15	325 / 22.4	3000 / 207	1800 / 51
B15 - 63 / 4000	CAT C15	310 / 21.4	4000 / 276	1650 / 47
B18 - 62 / 2175	CAT C18	350 / 24	2175 / 150	2700 / 76.5
B18 - 63 / 3000	CAT C18	325 / 22.4	3000 / 207	1900 / 54
B18TT - 61 / 1000	CAT C18 Twin Turbo	350 / 24	1000 / 69	4500 / 128
B18TT - 64 / 5000	CAT C18 Twin Turbo	350 / 24	5000 / 345	1970 / 56

Containerized Model	Engine	Suction P (psi / bar)	Discharge P (psi / bar)	Capacity @ Suction P (cfm / m3/min)
B15 - 62 / 2175 weatherproof	CAT C15	350 / 24	2175 / 150	2250 / 64
B18 - 62 / 2175 weatherproof	CAT C18	350 / 24	2175 / 150	2700 / 76.5
B18 - 62 / 2250 rig safe	CAT C18	350 / 24	2250 / 155	2185 / 62
B18 - 63 / 3000 rig safe	CAT C18	325 / 22.4	3000 / 207	1900 / 54
B18TT - 64 / 5000 rig safe	CAT C18 Twin Turbo	350 / 24	5000 / 345	1970 / 56
XAS375 rig safe	CAT C4.4	Atmosphere	100 / 7	375 / 11
XATS1020 Zone2	CUM QSM11 ATEX	Atmosphere	150 / 10.3	1020 / 29
XRVO1550 Zone2	CAT C32 ATEX	Atmosphere	365 / 25	1550 / 44
B9 - 64 / 5000 Zone2	CAT C9 ATEX	320 / 22	5000 / 345	755 / 21

Screwbooster Model	Engine	Screw Compressor (psi / bar)	Discharge P (psi / bar)	Capacity (cfm / m3/min)
SB7 - 44 / 2000	CAT C7	Atmosphere to 160 / 11	2000 / 138	320 / 9
SB13 - 44 / 2500	CAT C13	Atmosphere to 150 / 10	2500 / 172	600 / 17
SB15 - 44 / 1500	CAT C15	Atmosphere to 150 / 10	1500 / 104	800 / 23
SB18 - 44 / 2700	CAT C18	Atmosphere to 165 / 12	2700 / 186	800 / 23
SBM12 - 44 / 3000	CAT C12 marine	Atmosphere to 150 / 10	3000 / 207	500 / 14
SBM18 - 44 / 2700	CAT C18 marine	Atmosphere to 165 / 12	2700 / 186	800 / 23

PTO / OEM Model	Engine	Screw Compressor (psi / bar)	Discharge P (psi / bar)	Capacity (cfm / m3/min)
M - 41 / 1000	N/A	350 / 24	1000 / 69	2440 / 69
M - 85A / 2000	CUM V903	Atmosphere	2000 / 138	600 / 17

*For US, Canada, Europe and Japan

** For countries other than US, Canada, Europe and Japan

Sustainable Productivity

Atlas Copco



M - 41



B4 - 41



B7-41



B18 - 62



SB7 - 44



SBM18 - 44



B18 - 62 Rig Safe



B18 - 62 Weatherproof



XATS 1020 Zone2

Standard features:

- Automatic load/unload system
- On board fuel tank
- Booster bypass manifold (single and 2-stage only)
- Engine speed adjustment
- Double acting concentric valves
- Watercooled booster block
- Low pressure switch at booster inlet
- Precooler and suction scrubber tank
- Intercoolers and scrubber tanks (multi-stage models)
- Aftercooler
- Open skid with four point lifting*
- 24 volt DC starting and operating system
- Suction, interstage (multi-stage models) and discharge safety relief valves
- Full function instrument panel monitoring all pressures, temperatures and controls with full protection shutdown and fault indicators

Options:

- Digital control panel
- Automatic scrubber drain valve
- Cold weather kit
- Manual louvers in front of coolers
- Airstarter
- Spark arrestor
- Overspeed shutdown valve
- Inlet particle filter
- Lights for night operation
- Weatherproof container
- Service packs 250/500/1000/2000 hours
- Valve and piston kits

Other options, pressures, capacities: available on request

*B4-41 and B7-41 have single point lifting

Service You Can Rely On

Global Network – The Atlas Copco service organization is established in over 160 countries. Local customer centers and fully equipped mobile service vans are an integral part of the aftermarket network.

Advanced Technical Support – More than 1700 service technicians are continuously trained and updated on the latest product developments and servicing methods.

World Class Logistics – Genuine parts are delivered to your doorstep in record times, wherever you are.



Atlas Copco Hurricane LLC
Part of the Atlas Copco Group
Phone: +1 (317) 736-3800
www.atlascopco.com/hurricane